## Listing of Claims

This listing of claims will replace all prior versions of claims and listings of claims in the application:

- (Currently Amended) A monitoring system for distributed utilities, the monitoring system comprising;
  - a generation device for converting an available resource to a desired utility, the generation device characterized by a plurality of operating parameters;
  - b. an input sensor for measuring input to the generation device;
  - an output sensor for measuring consumption of output from the generation device:
  - d. a <u>local</u> controller for concatenating measured input and consumption of output on the basis of the input and output sensors; and
  - a remote controller for modifying operation of the generation device based on the concatenated measured input and consumption of output.
- (Original) A monitoring system according to claim 1, further comprising at least one sensor for measuring at least one parameter of the said plurality of operating parameters of the generation device.
- (Currently Amended) A monitoring system according to claim 2 [[1]], wherein the at least one sensor is a heat transfer monitor.
- (Currently Amended) A monitoring system according to claim 2 [[1]], wherein the at least one sensor is a flow impedance monitor.
- (Original) A monitoring system according to claim 1, wherein the generation device is a water purifier.
- (Currently Amended) A monitoring system according to claim 1 [[6]], wherein the input sensor is a flowrate monitor.

- (Currently Amended) A monitoring system according to claim 6, wherein the output sensor includes a water quality sensor including at least one of a <u>turbidity turpidity</u>, conductivity, and temperature sensor.
- (Original) A monitoring system according to claim 7, further comprising a shut off switch
  that automatically turns off said generation device when said water quality sensor rises
  above a pre-programmed water quality value.
- (Original) A monitoring system according to claim 7, further comprising an alarm that alerts a user when said water quality value rises above a pre-programmed water quality value.
- (Original) A monitoring system according to claim 7, further comprising a remotely operable shut off switch.
- (Original) A monitoring system according to claim 1, wherein the generation device is an electrical power generator.
- 12. (Original) A monitoring system according to claim 11, wherein the input sensor includes a fuel consumption rate monitor.
- (Original) A monitoring system according to claim 11, wherein the output sensor includes an electrical usage meter monitor.
- 14. (Original) A monitoring system according to claim 1, further comprising a telemetry module for communicating measured input and output parameters to a remote site.
- 15. (Original) A monitoring system according to claim 14, wherein the telemetry module is a cellular communications system.

Appl. No. 10/566,307 Amdt. Dated July 18, 2007

Reply to Office Action of April 18, 2007

Reply to Office Action of April 18, 2007

- 16. (Original) A monitoring system according to claim 14, wherein the telemetry module is a wireless system.
- 17. (Original) A monitoring system according to claim 1, further including a remote actuator for varying operating parameters of the generator based on remotely received instructions.
- 18. (Original) A monitoring system according to claim 1, further including a self-locating device having an output indicative of the location of the monitoring system.
- (Original) A monitoring system according to claim 18, wherein the self-locating device is a global positioning system.
- 20. (Original) A monitoring system according to claim 18, wherein monitored characteristics of input and output depend upon the location of the monitoring system.
- 21. (Currently Amended) A method for assembling a monitoring system comprising:
  - a. providing a generation device;
  - b. coupling an input sensor for measuring input to the generation device;
  - c. coupling an output sensor for measuring consumption of output from the generation device; and
  - coupling a <u>local</u> controller to the input and output sensor for concatenating measured input and consumption of output on the basis of the input and output sensors; and
  - e. providing a remote controller for modifying operation of the generation device based on the concatenated measured input and consumption of output.
- 22. (Original) The method of claim 21, further comprising:
  - a. providing communication between a telemetry module and said controller; and
  - b. providing communication between said telemetry module and a monitoring station

- 23. (Currently Amended) A distributed network of utilities, including at least one of a source of purified water and a source of electrical power, the distributed network comprising:
  - a. generators for converting a resource into a useful utility;
  - b, input sensors for measuring inputs to respective generators;
  - c. output sensor for measuring consumption of output from respective generators;
  - a telemetry transmitter for transmitting input and output parameters of a specified generator; and
  - a remote <u>controller processor</u> for receiving input and output parameters from a
    plurality of utility generators <u>and modifying operation of the generators based on</u>
    the measured input and consumption of output
- 24. (Original) A method for providing distributed utilities, the method comprising:
  - a. providing a generator to a user;
  - b. monitoring at least one index of generator usage to supply a utility; and
  - c. charging the user on the basis of the index of generator usage.